
State of California Office of Emergency Services

FIRE AND RESCUE DIVISION



OPERATOR'S MANUAL

FIRE APPARATUS Model 1950-B

Series No. 208 through 212

STATISTICAL INFORMATION

ENGINE AND CHASSIS

MAKE: INTERNATIONAL

MODEL: 1950B CARGOSTAR

YEAR: OES

208-212

1984

ENGINE: INTERNATIONAL

MODEL: DT466C/210 HP

CRANKCASE CAPACITY:

16 QUARTS WITH FILTER

ENGINE OIL:

S.A.E. #30 - USE OILS MEETING THE FOLLOWING ENGINE SERVICE

CLASSIFICATION

CD/SF OR CD/SE

(MIL - L - 46152B AND MIL -L-2104D)

FUEL TYPE:

DIESEL (MINIMUN CETANE RATING OF 40)

FUEL COPACITY:

100 GALLONS

(50 GALLONS LEFT/50 GALLONS RIGHT)

NOTE: TANKS ARE EQUALIZED

AIR CLEANER:

TWO-STAGE, DRY TYPE

(REFER TO ENGINE MANUAL FOR SERVICE INSTRUCTIONS)

COOLING SYSTEMS CAPACITY: APPROXIMATELY 50 QUARTS

SYEERING:

INTEGRAL POWER STEERING (DEXTRON II - TYPE XT-2

QDX OR EQUIVALENT)

REAR AXLE:

2-SPEED EATON MODEL: 23221

RATIOS:

4.88/6.64 RATED CAPACITY 23,000#

TRANSMISSION CAPACITY:

18 PINTS TRANSMISSION OIL: S.A.E. 50

DIFFERENTIAL:

S.A.E. #90 GEAR OIL

TIRES:

1100 X 20, 14-PLY PRESSURE: 85 PSI

STATISTICAL INFORMATION (Continued)

FIRE BODY AND PUMPS

BODY BUILDUP:

WESTATES

MAIN PUMP:

WATEROUS

MODEL: CSMB-1000

RATING:

1000 GPM - SINGLE STAGE

BOOSTER PUMP: WATEROUS MODEL: CPK-2-300 (PTO-DRIVE)

RATING:

300 GPM - 150 PSI

NOTE: DAMAGE WILL OCCUR IF BOOSTER PUMP IS OPERATED IN EXCESS OF 2,600 ENGINE

WATER TANK CAPACITY: 750 GALLONS

TANK CONSTRUCTION: CROSSLINK/POLYURETHANE

REFER TO WATEROUS PUMP MANUAL FOR MAINTENANCE INSTRUCTIONS. NOTE:

State of California OFFICE, OF EMERGENCY SERVICES Fire and Rescue Division

EXHIBIT "A" - EQUIPMENT INVENTORY

OI ID LITE	LICENSE NUMBER:	MITIMIPLED	MOTOR NUMBER:	
WRENCH, HOSE WRENCH, HARD STRAP, HOSE LANTERN, HAN RADIO, MOBIL RADIO, MOBIL BOOK, RADIO MALLET, RUBB CUTTER, BOLT SHOVEL BAR, CROW HAMMER, SLEDE KIT, REFLECTO	W/STREAM STRAIGHTENER -1/2" - 1-3/4" - 2" EDIT CARD JISHER 4# OR 5# IT N HOSE 2-1/2" X 12' DISCHARGE ' SUCTION /2" IPF TO 1-1/2" NSM /2" NSF TO 1-1/2" PCM /2" NSF TO 1-1/2" IPM 1/2" DF /2" NSF TO 1-1/2" NSM /2" STABLE HYDRANT SPANNER SUCTION HOSE SPANNER & LADDER D, 6 VOLT E SER. # OES # E SER. # OES # MAINTENANCE LOG ER GE OR, 3-UNIT IES TO OES ENGINES 201 AND U	8 HOSE, 1" 1 CLAMP, H 1 PIKE POL 1 LADDER, 1 LADDER, 1 HOSE, SO 1 KIT, RAD 1 AXE, PIC BRACKET 1 MANUAL, 1 MANUAL, 1 MANUAL, 1 OES OPER 1 OES BULL 1 FLOTO PUR	NST 50' LENGTH HOSE (HEBERT) LE 24' EXTENSION 14' ROOF LEF LEF LEF LEF LEF LEF LEF LEF LEF LE	NSM
PARTMENT:		DATE	:	